

JLG

E600JP

Articulating Boom Lift



Key Specs

- Platform Height: 18.39 m / 60 ft
- Machine Width: 2.42 m / 8 ft

Power Source

Batteries	8 x 6V, 415 A-h
Electrical System	48 Volts DC

Performance Data

Drive Speed - Platform Lowered	4.80 km/h / 2.98 mph
Gradeability - 2WD	30 %
Gradeability - 4WD	45 %
Platform Capacity	230 kg / 507 lb
Swing	400 Degrees
Swing Type	Non-Continuous
Turning Radius - Outside	4.64 m / 15 ft

Dimensional Data

Ground Clearance	0.3 m / 1 ft
Machine Height	2.54 m / 8 ft
Machine Length	10.15 m / 33 ft
Machine Width	2.42 m / 8 ft
Platform Dimension A	0.76 m / 2 ft
Platform Dimension B	1.83 m / 6 ft
Platform Height	18.39 m / 60 ft
Tailswing	1.23 m / 4 ft
Tyre Size	36 x 14-22.5 Non-marking Pneumatic
Wheelbase	2.74 m / 9 ft

Reach Specifications

Horizontal Jib Rotation	180 Degrees
Horizontal Outreach	13.54 m / 44 ft
Platform Height	18.39 m / 60 ft
Working Height	20.39 m / 67 ft
Working Outreach	14.19 m / 47 ft

General Specifications

Capacity - Hydraulic Reservoir

60 L / 16 gal.

Machine Weight

7144 kg / 15750 lb

Key Features

- Highest electric boom in the industry
- Environmentally friendly – low emissions, reduced noise and standard non-marking tyres
- Maneuverability – move over uneven surfaces with the Automatic Traction Control option
- Productivity – work longer with longer duty cycles

Reach

